

## IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of the claims in the application.

1. (*Original*) A method for converting a shower to a combination shower and spray bar, the method comprising:
  - removing an existing showerhead from a water supply outlet;
  - attaching an inlet of a 3-way connector to the water supply outlet, wherein the 3-way connector has a first outlet and a second outlet;
  - connecting a showerhead to the first outlet of the 3-way connector;
  - connecting a spray bar to the second outlet of the 3-way connector, wherein the spray bar comprises a plurality of spray nozzles for projecting a plurality of water streams toward a bathing position; and
  - securing the spray bar on or adjacent a vertical surface near the bathing position.
2. (*Original*) The method according to claim 1, wherein the step of securing comprises retaining the spa spray bar within a clamp adapted for receiving an outer diameter of the spray bar.
3. (*Original*) The method according to claim 2, wherein the clamp is attached to the wall by suction, adhesive or permanent attachment means.
4. (*Original*) The method according to claim 1, further comprising inserting a flow control valve between the water supply outlet and the showerhead.
5. (*Original*) The method according to claim 4, wherein the flow control valve is incorporated into the first outlet of the 3-way connector
6. (*Original*) The method according to claim 1, further comprising inserting a flow control valve between the second outlet of the 3-way connector and the spray bar.

-3-

7. *(Original)* The method according to claim 1, further comprising inserting one or more swivel joints between the second outlet of the 3-way connector and the spray bar.

8. *(Original)* The method according to claim 1, wherein the spray bar comprises a plurality of telescoping sections.

9. *(Original)* The method according to claim 1, wherein the spray bar comprises a plurality of sections connected by one or more swivel joints.

10. *(Original)* An assembly kit for converting an existing showerhead on a pre-existing water source outlet into a combination showerhead and spray bar, the assembly comprising:

- a 3-way connector for mounting on the water source outlet after removal of the existing showerhead, the 3-way connector having a first outlet and a second outlet;
- a pipe joint for connecting the first outlet to a showerhead;
- at least one connector pipe connected to the second outlet of the 3-way connector, the at least one connector pipe having an outlet end;
- a spray bar connected to the outlet end of the at least one connector pipe, the spray bar having a plurality of nozzles adapted to produce a plurality of water streams projected toward a bathing position; and
- at least one mounting device for affixing the spray bar on or adjacent a vertical surface near the bathing position.

11. *(Original)* The assembly according to claim 10, wherein the mounting device comprises a clamp adapted for receiving an outer diameter of the spray bar and a fastening means.

12. *(Original)* The assembly according to claim 11 wherein the fastening means comprises a suction cup or an adhesive.

13. *(Original)* The assembly according to claim 10, wherein the at least one connector pipe comprises a first connector pipe and a second connector pipe and further

-4-

comprising a swivel joint disposed between each of the second outlet of the 3-way connector and the first connector pipe, the first connector pipe and the second connector pipe, and the second connector pipe and the spray bar.

14. (*Original*) The assembly according to claim 10, further comprising a flow control valve disposed between the at least one connector pipe and the spray bar.

15. (*Original*) The assembly according to claim 10, further comprising a flow control valve disposed between the first outlet of the 3-way connector and the pipe joint.

16. (*Original*) The assembly according to claim 10, wherein the spray bar comprises a plurality of telescoping sections.

17. (*Original*) The assembly according to claim 10, wherein the spray bar comprises a plurality of sections connected by one or more swivel joints.

18. (*Original*) An assembly for converting an existing showerhead on a pre-existing water source outlet into a combination showerhead and spray bar, the assembly comprising:

- a 3-way connector for mounting on the water source outlet after removal of the existing showerhead, the 3-way connector having a first outlet and a second outlet;
- a pipe joint for connecting the first outlet to a showerhead;
- a first flow control valve disposed between the first outlet of the 3-way connector and the pipe joint;

- at least one connector pipe connected to the second outlet of the 3-way connector, the at least one connector pipe having an outlet end;

- at least one swivel joint disposed between the second outlet of the 3-way connector and the outlet end of the at least connector pipe;

- a spray bar connected to the outlet end of the at least one connector pipe, the spray bar having a plurality of nozzles adapted to produce a plurality of water streams projected toward a bathing position;

- a second flow control valve disposed between the at least one connector pipe and the spray bar;

-5-

at least one mounting device for affixing the spray bar on or adjacent a vertical surface near the bathing position, the mounting device comprising a clamp adapted for receiving an outer diameter of the spray bar and an fastening means.

19. (*Currently amended*) The assembly according to claim ~~13~~ 18, wherein the fastening means comprises a suction cup or an adhesive.

20. (*Currently amended*) The assembly according to claim ~~13~~ 18, wherein the at least one connector pipe comprises a first connector pipe and a second connector pipe and wherein the at least one swivel joint comprises a first swivel joint disposed between the second outlet of the 3-way connector and the first connector pipe, a second swivel joint disposed between the first connector pipe and the second connector pipe, and a third swivel joint disposed between the second connector pipe and the spray bar.